
Scalable Data Management Using Metadata and Provenance

Ethan Miller* • Darrell Long* • Margo Seltzer†

*UC Santa Cruz and †Harvard University





HARVARD

School of Engineering and Applied Sciences



Motivation

- HEC file systems are growing
 - Store petabytes (soon exabytes?) of data
 - Contain 109– 10¹⁰ files, if not more
- Hierarchical name spaces don't scale sufficiently
 - Namespace must become both broad and tall
 - Names are "static": difficult to assign multiple names to a single file
- Hierarchical name spaces are becoming difficult to use
 - File names often encode file properties
 - Users are starting to ignore the "real" file name
 - Obtain it via DB search and copy it to application





Project vision

- Goal: combine metadata gathering and indexing with search to build an extensible name space
 - Files are indexed automatically (and quickly!)
 - · The index is the only file-tracking structure in the system
 - Files can be linked to one another
 - Links may be automatically generated or user-created
 - All file names and directories are search queries
- Benefits
 - Flexible file system naming
 - Find files based on names and characteristics
 - No disconnect between naming and search
 - Personalized name spaces can be created
 - Incorporation of provenance with other metadata: simplifies file management
 - Scalable name space: handles billions of files
 - Simpler & more efficient: one FS structure, not parallel structures









- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!
 - Spotlight is too slow and doesn't scale well





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!
 - Spotlight is too slow and doesn't scale well
 - Neither includes provenance or locality-based search





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!
 - Spotlight is too slow and doesn't scale well
 - Neither includes provenance or locality-based search
- Challenging because





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!
 - Spotlight is too slow and doesn't scale well
 - Neither includes provenance or locality-based search
- Challenging because
 - Existing approaches don't scale well
 - Amount of metadata
 - Performance & reliability
 - Namespace size





- Similar approaches are already coming for
 - The Web: Google
 - Desktops: Spotlight
- Existing solutions have issues
 - Google uses too much hardware!
 - Spotlight is too slow and doesn't scale well
 - Neither includes provenance or locality-based search
- Challenging because
 - Existing approaches don't scale well
 - Amount of metadata
 - Performance & reliability
 - Namespace size
 - File names are firmly entrenched: need backwards compatibility





Research thrusts

- Three main research thrusts in this project
- Gathering and managing metadata
 - File properties
 - File content
 - Provenance
- Metadata index construction and management
- File naming & search





Gathering and managing metadata

- Need to efficiently gather metadata
 - Straightforward for single-node files
 - More difficult to index content of a multi-gigabyte file
- Gathering provenance across a large-scale HEC system can also be difficult
- Need to provide an efficient, easy-to-use API for users and applications to provide metadata
 - Content-based
 - User-defined tags
 - Links between files





Indexing metadata


- HEC file systems have billions (109–1010) of files
 - Each file can require 1–100KB (or more) of metadata
 - Total index size is many terabytes
- Performance is critical
 - Search-based naming will be the only name lookup scheme
 - Existing database-style solutions aren't fast enough
- Our goal: leverage file system characteristics to build a fast, efficient index
 - Attribute locality
 - Search locality





Spyglass: namespace partitioning

- Partition the index using the namespace
- Parts of the namespace are indexed in separate partitions
 - Exploits spatial locality
 - Allows index control at the granularity of sub-trees
 - Uses a simple greedy algorithm
- Partitions are stored sequentially on disk
 - Fast access to each partition








Spyglass: namespace partitioning

- Partition the index using the namespace
- Parts of the namespace are indexed in separate partitions
 - Exploits spatial locality
 - Allows index control at the granularity of sub-trees
 - Uses a simple greedy algorithm
- Partitions are stored sequentially on disk
 - Fast access to each partition







Spyglass: partition design


- Each partition stores metadata in a KD-tree
- Not explicitly tied to a particular index structure
- KD-trees
 - A multi-dimensional binary tree
 - Provides fast, multi-dimensional search
 - Allows a single index structure to be used
- Performance is bound by reading partitions from disk
- Partitions are managed by a caching sub-system
 - Uses LRU
 - Captures the likely Zipf-like query distributions
 - Ensures popular partitions are in-memory





Ongoing indexing work

- Expand cluster-based indexing to non-hierarchical file systems
 - Develop good approaches for clustering into sub-indexes
 - Ensure that clustered indexing scales: leverage locality
- Explore techniques for fast updating of indexes
 - Use index structures that can be efficiently updated?
 - Periodically rebuild indexes?
- Improve efficiency
 - Use Bloom filters (summaries) to query fewer clusters
 - Prune metadata and provenance to limit index size
 - Use NVRAM (flash, phase-change) for indexes
- Improve reliability





Searching and naming

- Replace hierarchical naming with dynamic names
 - Names are queries into the metadata index
 - Queries have to be fast!
- Challenges
 - Simple names for simple queries
 - Expressive, flexible language for complex queries
 - Allow searches across metadata, provenance, and file relationships
 - Language must allow for extensible names
 - File system can't dictate metadata schema
 - Different users will want different names
- Extend early work (PQL, QUASAR) to develop a usable naming scheme





Project plans

- Develop integrated index in a metadata server for an existing file system (e.g., PVFS, Ceph)
 - MDS can be tested on its own in the lab
 - MDS can be moved to the field (after sufficient hardening)
- Explore approaches to scalability & partitioning
 - Algorithms for scalable metadata gathering and indexing
 - Factors that impact scalability & partitioning effectiveness
 - Use of non-volatile memory to improve performance
- Develop methods to use provenance to guide workflow
- Investigate techniques for per-user customization of the name space and index
 - Provenance & security
 - Per-user usage history and preferences
- Refine a path query language




Questions?

UC Santa Cruz Storage Systems Research Center



Ethan Miller



Darrell Long



Harvard SYRAH lab






Margo Seltzer





Questions?

- These are project goals
 - We've done some early work on these areas
 - Much remains to be done





Ethan Miller



Darrell Long




Harvard SYRAH lab

Margo Seltzer



Questions?

- These are project goals
 - We've done some early work on these areas
 - Much remains to be done
- Feedback is welcome!





Ethan Miller



Darrell Long



Harvard SYRAH lab

Margo Seltzer

